TRP Mega Wash

Paccar Australia Pty. Ltd.

Safety Data Sheet according to WHS and ADG requirements

Chemwatch: 5168-11 Issue Date: 07/07/2015 Version No: 3.1.1.1 Print Date: 23/03/2016

Chemwatch Hazard Alert Code: 3

Initial Date: Not Available S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier	
Product name	TRP Mega Wash
Synonyms	pre-soak cleaner
Proper shipping name	CORROSIVE LIQUID, N.O.S. (contains sodium hydroxide)
Other means of identification	Not Available
Relevant identified uses of th	e substance or mixture and uses advised against
Relevant identified uses	Pre-soak cleaner for touchless truck washing.
Details of the supplier of the safety data sheet	
Registered company name	Paccar Australia Pty. Ltd.
Address	20 Canterbury Road Bayswater VIC 3152 Australia
Telephone	03 9721 1500
Fax	Not Available
Website	www.paccar.com.au
Email	Not Available
Emergency telephone number	
Association / Organisation	Poisons information Line
Emergency telephone numbers	131 126
Other emergency telephone numbers	Not Available
SECTION 2 HAZARDS ID	ENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

Min Max	
	0 = Minimum
	1 = Low 2 = Moderate
	3 = High
	4 = Extreme
	MinMax_

Poisons Schedule	S5
[1] Classification	Metal Corrosion Category 1, Skin Corrosion/Irritation Category 1B, Serious Eye Damage Category 1, Chronic Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI
Label elements	·
GHS label elements	
SIGNAL WORD	DANGER
Hazard statement(s)	
H290	May be corrosive to metals.

	TRP Mega	
Chemwatch: 5168-11	Page 2 of 13	Issue Date: 07/07/2015
Version No: 3.1.1.1		Print Date: 23/03/2016
H314	Causes severe skin burns and eye damage.	
H318	Causes serious eye damage.	
H412	2 Harmful to aquatic life with long lasting effects.	
Precautionary statement(s)) Prevention	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P234	Keep only in original container.	
P273	Avoid release to the environment.	
Precautionary statement(s)	Response	
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.	
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rin	nsing.
P310	Immediately call a POISON CENTER or doctor/physician.	

P310	Immediately call a POISON CENTER or doctor/physician.
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Precautionary statement(s) Storage	
P405	Store locked up.
Precautionary statement(s) Disposal	
P501	Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
1310-73-2	5-10	sodium hydroxide
6834-92-0	<10	sodium metasilicate, anhydrous
Not Available	<10	alkaline salts.
68989-03-7	3-6	guaternary cocoamine dimethyl sulfate, ethoxylated
Not Available	3-6	Ingredients determined not to be hazardous
7732-18-5	>60	water

SECTION 4 FIRST AID MEASURES

Description of first aid measures		
	Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
S	Skin Contact	 If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.

Chemwatch: 5168-11
Version No: 3111

Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully.
	 Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute or short-term repeated exposures to highly alkaline materials:

- Respiratory stress is uncommon but present occasionally because of soft tissue edema.
- Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
- Oxygen is given as indicated.
- The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
- Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue. Alkalis continue to cause damage after exposure.

INGESTION:

- Milk and water are the preferred diluents
- No more than 2 glasses of water should be given to an adult.
- Neutralising agents should never be given since exothermic heat reaction may compound

injury. * Catharsis and emesis are absolutely contra-indicated.

* Activated charcoal does not absorb alkali.

* Gastric lavage should not be used.

- Supportive care involves the following:
- Withhold oral feedings initially.
- If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing

(dysphagia). SKIN AND EYE:

- Injury should be irrigated for 20-30 minutes.
- Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology]

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of

combustible substances. In such an event consider: • foam. • dry chemical powder. • carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.		
Advice for firefighters			
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use fire fighting procedures suitable for surrounding area. Do not approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. 		
Fire/Explosion Hazard	 The material is not readily combustible under normal conditions. However, it will break down under fire conditions and the organic component may burn. Not considered to be a significant fire risk. Heat may cause expansion or decomposition with violent rupture of containers. Decomposes on heating and may produce toxic fumes of carbon monoxide (CO). May emit acrid smoke. 		

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	 Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. Check regularly for spills and leaks. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling.

Personal Protective Equipment advice is contained in Section 8 of the SDS. SECTION 7 HANDLING AND STORAGE

Precautions for safe handling	g
Safe handling	 DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with moisture. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS. DO NOT store near acids, or oxidising agents No smoking, naked lights, heat or ignition sources.
contanione for care storage,	
Suitable container	 Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. For low viscosity materials Drums and jerricans must be of the non-removable head type. Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): Removable head packaging; Cans with friction closures and low pressure tubes and cartridges may be used. Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
Storage incompatibility	► Avoid strong acids, acid chlorides, acid anhydrides and chloroformates. ► Avoid contact with copper, aluminium and their alloys.

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	sodium hydroxide	Sodium hydroxide	Not Available	Not Available	2 mg/m3	Not Available
EMERGENCY LIMITS						
Ingredient	Material name		TEEL-1	TEEL-2		TEEL-3

sodium hydroxide Sodium hydroxide Not Available Not Available Not Available sodium metasilicate. Sodium metasilicate pentahydrate 45 mg/m3 45 mg/m3 170 mg/m3 anhydrous sodium metasilicate, Sodium silicate; (Sodium metasilicate) 18 mg/m3 230 mg/m3 230 mg/m3 anhydrous Revised IDLH Ingredient **Original IDLH** sodium hydroxide 250 mg/m3 10 mg/m3 sodium metasilicate, Not Available Not Available anhydrous alkaline salts. Not Available Not Available quaternary cocoamine dimethyl sulfate, ethoxylated Not Available Not Available Ingredients determined not to Not Available Not Available be hazardous Not Available Not Available water Exposure controls Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The Appropriate engineering basic types of engineering controls are: controls Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Personal protection Chemical goggles. • Full face shield may be required for supplementary but never for primary protection of eyes. • Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the Eve and face wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and protection adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Skin protection See Hand protection below • Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of guality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when Hands/feet protection making a final choice. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: frequency and duration of contact, chemical resistance of glove material, glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.

 • wree only price contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.

 Body protection
 See Other protection below

 • Overalls.
 • Overalls.

 • PVC Apron.
 • PVC Apron.

 • Eyewash unit.
 • Ensure there is ready access to a safety shower.

 Thermal hazards
 Not Available

TRP Mega Page 6 of 13

Recommended material(s)

GLOVE SELECTION INDEX

Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent) Glove selection is based on a modified presentation of the:

Material	СРІ	modified presentation of the:
BUTYL	С	Required Minimum Half-Face Full-Face Powered Air Protection Factor Respirator Respirator Respirator
NAT+NEOPR+NITRILE	С	
NATURAL RUBBER	С	up to 10 x ES AK-AUS P2 - Class 1 P2
NATURAL+NEOPRENE	С	up to 50 x ES - Class -
NEOPRENE	С	1 P2
NEOPRENE/NATURAL	С	up to 100 x ES - AK-2 P2 AK-PAPR-2 P2 ^
NITRILE	С	"Forsberg Clothing Performance Index". Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the
NITRILE+PVC	С	The effect(s) of the following substance(s) are taken into account in the <i>computer</i> - "Exposure Standard" (or ES), respiratory protection is required.
PE	С	generated selection: Degree of protection varies with both face-piece and Class of filter; the nature of
PE/EVAL/PE	С	protection TRP Mega Wash varies
PVA	С	with Type of filter.
PVC	С	^ - Full-face A/All classes) = Organic vanours, B ALIS or B1 = Acid gasses, B2 = Acid gas or hydrogen
SARANEX-23	С	cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Arricultural chemicals. K = Ammonia(NH3), Ha = Mercury. NO = Oxides of nitrogen MB =
SARANEX-23 2-PLY	С	Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)
TEFLON	С	
VITON	С	
VITON/CHLOROBUTYL	С	

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final

selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information	on basic	physical	and chemica	I properties
mormation	on busic	priysicai	and onemica	i properties

Appearance	Light straw coloured liquid with amine odour; mixes with wa	ter.	
Physical state	Liquid	Relative density (Water = 1)	~1.1
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	12.1	Decomposition temperature	Not Available
Melting point / freezing point (°C)	~0	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	~100	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available

Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	2.37 @ 20 degC	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological eff	ects	
Inhaled	Not normally a hazard due to non-volatile nature of product Inhaling corrosive bases may irritate the respiratory tract. Symptoms inclu	ude cough, choking, pain and damage to the mucous membrane.
Ingestion	The material can produce chemical burns within the oral cavity and gas Accidental ingestion of the material may be damaging to the health of the	trointestinal tract following ingestion. individual.
Skin Contact	The material can produce chemical burns following direct contact with the Open cuts, abraded or irritated skin should not be exposed to this materia Entry into the blood-stream, through, for example, cuts, abrasions or lesic prior to the use of the material and ensure that any external damage is su This material can cause inflammation of the skin on contact in some personal contact in some personal contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in some personal can be able to the skin on contact in the skin on contact	e skin. al ons, may produce systemic injury with harmful effects. Examine the skin uitably protected. sons.
Eye	The material can produce chemical burns to the eye following direct cont irritating. If applied to the eyes, this material causes severe eye damage.	tact. Vapours or mists may be extremely
Chronic	Repeated or prolonged exposure to corrosives may result in the erosion (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks or Substance accumulation, in the human body, may occur and may cause exposure. There is limited evidence that, skin contact with this product is compared to the general population.	of teeth, inflammatory and ulcerative changes in the mouth and necrosis f bronchial pneumonia may ensue. some concern following repeated or long-term occupational more likely to cause a sensitisation reaction in some persons
	TOXICITY	IRRITATION
TRP Mega Wash	Not Available	Not Available
	TOXICITY	IRRITATION
sodium hydroxide	Oral (rabbit) LD50: 325 mg/k ^[1]	Eye (rabbit): 0.05 mg/24h SEVERE
		Eye (rabbit):1 mg/24h SEVERE
		Eye (rabbit):1 mg/30s rinsed-SEVERE
		Skin (rabbit): 500 mg/24h SEVERE
	TOVICITY	
sodium metasilicate, anhydrous		IRRITATION

	TRP M	lega	
Chemwatch: 5168-11	Page 8	l of 13	Issue Date: 07/07/2015
Version No: 3.1.1.1			Print Date: 23/03/2016
	dermal (rat) LD50: >5000 mg/kg	Skin (hum	an): 250 mg/24h SEVERE
	Oral (rat) LD50: 600 mg/kg]	Skin (rabb	it): 250 mg/24h SEVERE
quaternary cocoamine dimethyl sulfate, ethoxylated	ΤΟΧΙCΙΤΥ	IRRITATIO	ИС
	Not Available	Not Availa	able
	ΤΟΧΙΟΙΤΥ	IRRITATIO	2N
water	[2] Oral (rat) LD50: >90000 mg/kgNot Available		
Legend:	 Value obtained from Europe ECHA Registered S specified data extracted from RTECS - Register of T 	Substances - Acute toxicity 2.* V oxic Effect of chemical Substance	'alue obtained from manufacturer's SDS. Unless otherwise
	The material may produce severe irritation to the ever conjunctivitis. The material may cause severe skin irritation after pi production of vesicles, scaling and thickening of the st Asthma-like symptoms may continue for months or e known as reactive airways dysfunction syndrome (RA for the diagnosis of RADS include the absence of preceding respirato within minutes to hours of a documented exposure to severe bronchial hyperreactivity on methacholine ch also been included in the criteria for diagnosis of RA related to the concentration of and duration of expos occurs as result of exposure due to high concentration exposure ceases. The disorder is characterised by d The material may cause severe skin irritation after pi production of vesicles, scaling and thickening of the Asthma-like symptoms may continue for months or e known as reactive airways dysfunction syndrome (RA for the diagnosis	causing pronounced inflammatic volonged or repeated exposure an skin. Repeated exposures may pr ven years after exposure to the m vDS) which can occur following exp ry disease, in a non-atopic individ to the irritant. A reversible airflow p allenge testing and the lack of mir DS. RADS (or asthma) following a ure to the irritating substance. Ind pispnea, cough and mucus produc rolonged or repeated exposure an skin. Repeated exposures may pr even years after exposure to the m ADS) which can occur following exp and the irritation occur following exp even years after exposure to the m and the irritation occur following exp expension.	nn. Repeated or prolonged exposure to irritants may produce id may produce on contact skin redness, swelling, the oduce severe ulceration. Interial ceases. This may be due to a non-allergenic condition posure to high levels of highly irritating compound. Key criteria ual, with abrupt onset of persistent asthma-like symptoms attern, on spirometry, with the presence of moderate to nimal lymphocytic inflammation, without eosinophilia, have an irritating inhalation is an infrequent disorder with rates lustrial bronchitis, on the other hand, is a disorder that varticulate in nature) and is completely reversible after citon. Ind may produce on contact skin redness, swelling, the roduce severe ulceration.
SODIOM METASILICATE, ANHYDROUS	of RADS include the absence of preceding respirato within minutes to hours of a documented exposure to severe bronchial hyperreactivity on methacholine ch also been included in the criteria for diagnosis of RA related to the concentration of and duration of expos occurs as result of exposure due to high concentratit exposure ceases. The disorder is characterised by c	y disease, in a non-atopic individ the irritant. A reversible airflow p allenge testing and the lack of mir DS. RADS (or asthma) following a ure to the irritating substance. Ind ons of irritating substance (often p lyspnea, cough and mucus produc	ual, with abrupt onset of persistent asthma-like symptoms battern, on spirometry, with the presence of moderate to simal lymphocytic inflammation, without eosinophilia, have an irritating inhalation is an infrequent disorder with rates lustrial bronchitis, on the other hand, is a disorder that branticulate in nature) and is completely reversible after ction.
QUATERNARY COCOAMINE DIMETHYL SULFATE, ETHOXYLATED & WATER	No significant acute toxicological data identified in lit	erature search.	
Acute Toxicity		Carcinogenio	sity
Skin Irritation/Corrosion	*	Reproductiv	vity
Serious Eye Damage/Irritation	*	STOT - Single Expos	sure
Respiratory or Skin sensitisation	0	STOT - Repeated Expos	ure
Mutagenicity		Aspiration Haza	ard
		Legend:	 Data available but does not fill the criteria for classification Data required to make classification available

Data required to make classification available
 Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity					
Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
sodium hydroxide	EC50	384	Crustacea	27901.643mg/L	3
sodium hydroxide	EC50	96	Algae or other aquatic plants	1034.10043mg/L	3
sodium hydroxide	LC50	96	Fish	4.16158mg/L	3
sodium hydroxide	NOEC	96	Fish	56mg/L	4

Chemwatch: 5168-11

Issue Date: 07/07/2015 Print Date: 23/03/2016

Version No: 3.1.1.1

sodium hydroxide	EC50	48	Crustacea	40.4mg/L	2
sodium metasilicate, anhydrous	EC50	96	Crustacea	160mg/L	1
sodium metasilicate, anhydrous	LC50	96	Fish	180mg/L	1
sodium metasilicate, anhydrous	EC50	48	Crustacea	1700mg/L	2
sodium metasilicate, anhydrous	EC50	72	Algae or other aquatic plants	207mg/L	2
water	EC50	384	Crustacea	199.179mg/L	3
water	EC50	96	Algae or other aquatic plants	8768.874mg/L	3
water	LC50	96	Fish	897.520mg/L	3
Legend:	Extracted from 1. IUC V3.12 - Aquatic Toxicity Data	LID Toxicity Data 2. Europe ECF (Estimated) 4. US EPA. Ecotox (, IA Registered Substances - Ecotoxicolog database - Aquatic Toxicity Data 5. ECET	ical Information - Aquatic Toxicity	3. EPIWIN Suite Data 6. NITE

Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved

. (Japan) -

waste sites. Prevent, by any means available, spillage from entering drains or water

courses. DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
sodium hydroxide	LOW	LOW
water	LOW	LOW
Bioaccumulative potential		
Ingredient	Bioaccumulation	
sodium hydroxide	LOW (LogKOW = -3.8796)	
water	LOW (LogKOW = -1.38)	
Mobility in soil		
Ingredient	Mobility	
sodium hydroxide	LOW (KOC = 14.3)	
water	LOW (KOC = 14.3)	

SECTION 13 DISPOSAL CONSIDERATIONS

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate:
Product / Packaging disposal Index of postance of a material may change in use, and recycling or reuse may not always be appropriate. • DO NOT allow wash water from cleaning or process equipment to enter drains. • It may be necessary to collect all wash water for treatment before disposal. • In all cases disposal to sever may be subject to local laws and regulations and these should be considered first. • Where in doubt contact the responsible authority. • Recycle wherever possible. • Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. • Treat and neutralise at an approved treatment plant. • Treat and neutralise at an approved treatment plant. • Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).

SECTION 14 TRANSPORT INFORMATION

Labels Required

	CORROSIVE 8				
Marine Pollutant	NO				
HAZCHEM	2X				
Land transport (ADG)					
UN number	1760				
Packing group					
UN proper shipping name	CORROSIVE LIQUID, N.O.S. (contains sodium hydroxide)				
Environmental hazard	Not Applicable				
Transport hazard class(es)	Class 8 Subrisk Not Applicable				
Special precautions for user	Special provisions 223 274 Limited quantity 5 L				
Air transport (ICAO-IATA / DO	GR)				
UN number	1760				
Packing group	III				
UN proper shipping name	Corrosive liquid, n.o.s. * (contains sodium hydroxide)				
Environmental hazard	Not Applicable				
Transport hazard class(es)	ICAO/IATA Class 8 ICAO / IATA Subrisk Not Applicable ERG Code 8L				
	Special provisions	A3A803			
	Cargo Only Packing Instructions	856			
	Cargo Only Maximum Qty / Pack	60 L			
Special precautions for user	Passenger and Cargo Packing Instructions	852			
usei	Passenger and Cargo Maximum Qty / Pack	5L			
	Passenger and Cargo Limited Quantity Packing Instruction	ns Y841			
	Passenger and Cargo Limited Maximum Qty / Pack	1L			
Sea transport (IMDG-Code / C	GGVSee)				
UN number	1760				
Packing group	III				
UN proper shipping name	CORROSIVE LIQUID, N.O.S. (contains sodium hydroxide)				
Environmental hazard	Not Applicable				
Transport hazard class(es)	IMDG Class 8 IMDG Subrisk Not Applicable				
Special precautions for user	EMS Number F-A, S-B Special provisions 223 274				

Limited Quantities 5 L
Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Version No: 3.1.1.1

Australia Inventory of Chemical Substances (AICS)

SECTION 15 REGULATORY INFORMATION

Safety,	health and	l environmental	regulations	/legislation	specific for	or the substance or I	nixture

SODIUM HYDROXIDE(1310-73-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards Australia Hazardous Substances Information System - Consolidated Lists

SODIUM METASILICATE, ANHYDROUS(6834-92-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Substances Information System - Consolidated Lists Australia Inventory of Chemical Substances (AICS)

QUATERNARY COCOAMINE DIMETHYL SULFATE, ETHOXYLATED(68989-03-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y

Page 12 of 13 TRP Mega

Print Date: 23/03/2016

Version No: 3.1.1.1

Canada - NDSL N (quaternary cocoamine dimethyl sulfate, ethoxylated; water; sodium metasilicate, anhydrous; sodium hydroxide) China - IECSC Y Europe - EINEC / ELINCS / N (quaternary cocoamine dimethyl sulfate, ethoxylated) NLP Japan - ENCS N (quaternary cocoamine dimethyl sulfate, ethoxylated; water) Korea - KECI Υ Y New Zealand - NZIoC Philippines - PICCS N (quaternary cocoamine dimethyl sulfate, ethoxylated) USA - TSCA Υ Y = All ingredients are on the inventory Legend: N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
sodium hydroxide	12200-64-5, 1310-73-2
quaternary cocoamine dimethyl sulfate, ethoxylated	197664-72-5, 307315-38-4, 68989-03-7

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Print Date: 23/03/2016

Version No: 3.1.1.1