Auto Klene Transan

Auto Klene Solutions Chemwatch: 5199-69 Version No: 2.1.1.1 Safety Data Sheet according to HSNO Regulations

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier	
Product name	Auto Klene Transan
Synonyms	detergent cleaner, sanitiser
Other means of identification	Not Available
Relevant identified uses of th	ne substance or mixture and uses advised against
Relevant identified uses	Detergent cleaner / sanitiser.
Details of the supplier of the	safety data sheet
Registered company name	Auto Klene Solutions
Address	1/83 Merrindale Drive VIC Croydon 3136 Australia
Telephone	+61 3 8761 1900
Fax	+61 3 8761 1955
Website	https://www.autoklene.com/msds/
Email	Not Available
Emergency telephone number	er
Association / Organisation	Not Available
Emergency telephone numbers	131 126 (Poisons Information Centre)
Other emergency telephone numbers	0800 764 766 (New Zealand Poisons Information Centre)
SECTION 2 HAZARDS ID	ENTIFICATION

Classification of the substance or mixture

Not considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

CHEMWATCH HAZARD RATINGS

		Min Max	<u> </u>	
Flammability	0		_	
Toxicity	1		_	0 = Minimum
Body Contact	1		_	1 = Low 2 = Moderate
Reactivity	0		_	3 = High
Chronic	0			4 = Extreme

Classification	Not Applicable
Determined by Chemwatch using GHS/HSNO criteria	Not Available
Label elements	
GHS label elements	Not Applicable

SIGNAL WORD | NOT APPLICABLE

Hazard statement(s)

Not Applicable

Not Applicable

Version No: 2.1.1.1

Auto Klene Transan Page 2 of 9

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name	
Not Available	10-30	nonionic surfactants, sequestrants and colouring agents, proprietary	
Not Available	0-5	quaternary compound, proprietary	
7732-18-5	balance	water	
SECTION 4 FIRST AID MEASURES			

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ► Immediately remove all contaminated clothing, including footwear. ► Flush skin and hair with running water (and soap if available). ► Seek medical attention in event of irritation.
Inhalation	► If fumes, aerosols or combustion products are inhaled remove from contaminated area. ► Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.
Indication of any immediate n	nedical attention and special treatment needed

ndication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances. In such an event consider: • foam. • dry chemical powder. • carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.

Auto Klene Transan Page 3 of 9

Fire/Explosion Hazard	 The material is not readily combustible under normal conditions. However, it will break down under fire conditions and the organic component may burn. Not considered to be a significant fire risk. Heat may cause expansion or decomposition with violent rupture of containers. Decomposes on heating and may produce toxic fumes of carbon monoxide (CO). May emit acrid smoke.
	Decomposes on heating and produces toxic fumes of:, carbon dioxide (CO2), other pyrolysis products typical of burning organic material
SECTION 6 ACCIDENTAL	RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	▶ Clean up all spills immediately.
	Avoid breathing vapours and contact with skin and eyes.
	▶ Control personal contact with the substance, by using protective equipment. ▶
	Contain and absorb spill with sand, earth, inert material or vermiculite.
	▶ Wipe up.
	▶ Place in a suitable, labelled container for waste disposal.
	Moderate hazard.
	▶ Clear area of personnel and move upwind.
	Alert Fire Brigade and tell them location and nature of hazard.
Major Spills	▶ Wear breathing apparatus plus protective gloves.
	▶ Prevent, by any means available, spillage from entering drains or water course.
	▶ Stop leak if safe to do so.

SECTION 7 HANDLING AND STORAGE

	▶ Avoid all personal contact, including inhalation.
	Wear protective clothing when risk of exposure occurs.
	▶ Use in a well-ventilated area.
Safe handling	Prevent concentration in hollows and sumps.
Sale handling	► DO NOT enter confined spaces until atmosphere has been checked.
	► DO NOT allow material to contact humans, exposed food or food utensils.
	Avoid contact with incompatible materials.
	DO NOT allow clothing wet with material to stay in contact with skin
	▶ Store in original containers.
	▶ Keep containers securely sealed.
0.1	▶ Store in a cool, dry, well-ventilated area.
Other information	▶ Store away from incompatible materials and foodstuff containers.
	Protect containers against physical damage and check regularly for leaks.
	Observe manufacturer's storage and handling recommendations contained within this SDS.
nditions for safe storage,	including any incompatibilities
	Polyethylene or polypropylene container.
Suitable container	▶ Packing as recommended by manufacturer.
Culturie Container	• Check all containers are clearly labelled and free from leaks.
Storage incompatibility	None known

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

- INGREDIENT DATA
- Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Auto Klene Multi Mix 2	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	
nonionic surfactants, sequestrants and colouring agents, proprietary	Not Available		Not Available	
quaternary compound, proprietary	Not Available		Not Available	

Chemwatch: 5199-69

Auto Klene Transan Page 4 of 9

Issue Date: 10/02/2016 Print Date: 27/06/2016

Not Available Not Available water Exposure controls Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Appropriate engineering Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically controls "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Personal protection Safety glasses with side shields. Chemical goggles Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the Eye and face wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and protection adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Skin protection See Hand protection below Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: frequency and duration of contact, Hands/feet protection chemical resistance of glove material, s glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. Body protection See Other protection below Overalls P.V.C. apron. Other protection Barrier cream. Skin cleansing cream. Eve wash unit Thermal hazards Not Available Recommended material(s)

GLOVE SELECTION INDEX

Auto Klene Multi Mix 2

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer-generated selection:

Material	СРІ
BUTYL	A
NEOPRENE	A
VITON	A
NATURAL RUBBER	С
PVA	С
* CPL - Chemwatch Performance Index	

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise beunsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Auto Klene Transan Page 5 of 9

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Light pink coloured semi-viscous liquid with neutral detergent - like odour; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	1.01
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	10.0-10.8	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	~100	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	7.5-8.5 (sol 1:80)
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7	
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur. 	
Possibility of hazardous reactions	See section 7	
Conditions to avoid	See section 7	
Incompatible materials	See section 7	
Hazardous decomposition products	See section 5	
SECTION 11 TOXICOLOGICAL INFORMATION		

Information on toxicological effects

Inhaled	There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.
Skin Contact	There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

emwatch: 5199-69 on No: 2.1.1.1		Auto Klene Transan Page 6 of 9	<u> </u>	Issue Date: 10/02/2016 Print Date: 27/06/2016
	ΤΟΧΙΟΙΤΥ		IRRITATION	
Auto Klene Multi Mix 2				
	Not Available		Not Available	

ΤΟΧΙΟΙΤΥ

water

 [2]
 Oral (rat) LD50: >90000 mg/kgNot Available

 Legend:
 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

IRRITATION

Auto Klene Multi Mix 2 & WATER	No significant acute toxicological data identified in literatur	e search.	
Acute Toxicity		Carcinogenicity	
Skin Irritation/Corrosion		Reproductivity	
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity		Aspiration Hazard	
		Legend: 🗙	 Data available but does not fill the criteria for classification Data required to make classification available Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
water	EC50	384	Crustacea	199.179mg/L	3
water	EC50	96	Algae or other aquatic plants	8768.874mg/L	3
water	LC50	96	Fish	897.520mg/L	3
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
water	LOW (LogKOW = -1.38)

Mobility in soil

Ingredient	Mobility	
water	LOW (KOC = 14.3)	

SECTION 13 DISPOSAL CONSIDERATIONS

Version No. 2.1.1.1

Auto Klene Transan Page 7 of 9

Waste treatment methods

Product / Packaging disposal

Recycle wherever possible or consult manufacturer for recycling options.
▶ Consult State Land Waste Management Authority for disposal.
Bury residue in an authorised landfill.
Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the disposal of material is carried out in accordance with Hazardous Substances (Disposal) Regulations 2001.

SECTION 14 TRANSPORT INFORMATION

Labels Required			
Marine Pollutant	NO		
HAZCHEM	Not Applicable		

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
Not Applicable	Not Applicable

WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Inventory of Chemicals (NZIoC)

Location Test Certificate

Subject to Regulation 55 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations, a location test certificate is required when quantity greater than or equal to those indicated below are present.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

Approved Handler

 Subject to Regulation 56 of the Hazardous Substances (Classes 1 to 5 Controls) Regulations and Regulation 9 of the Hazardous Substances (Classes 6, 8, and 9 Controls)

 Regulations, the substance
 the personal control of an Approved Handler when present in a quantity greater than or equal to those indicated below.

 Class of substance
 Quantities

 Not Applicable
 Not Applicable

Refer Group Standards for further information

Tracking Requirements

Not Applicable	
National Inventory	Status

Auto Klene Transan

Print Date: 27/06/2016

Version No: 2.1.1.1

Y Australia - AICS Y Canada - DSL Canada - NDSL N (water) China - IECSC Y Europe - EINEC / ELINCS / Υ NLP Japan - ENCS N (water) Korea - KECI Υ New Zealand - NZIoC Y Philippines - PICCS Y USA - TSCA Y Y = All ingredients are on the inventory Legend: N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Version No: 2.1.1.1

Print Date: 27/06/2016

Auto Klene Transan