

SAFETY DATA SHEET SUPER SHEEN

Product Name:

Date of Issue: JULY 2023 Page 1 of Total 6

SECTION 1 – STATEMENT OF CHEMICAL PRODUCT AND COMPANY IDENTIFICATION			
SUPPLIER:	Auto Klene Solutions Aust. Pty Ltd		
ADDRESS:	885 Mountain Highway, Bayswater, 3153 VIC		
Trade Name:	SUPER SHEEN		
TELEPHONE:	03 8761 1900	FAX:	03 8761 1955
AH EMERGENCY TELEPHONE:	1300 774 575 in Australia (M-F 7am-7pm)	Synonym:	SS
Substance:	Hydrocarbon based liquid	Product Use:	Tyre Rejuvenator
Creation Date:	July 2023	Revision Date:	July 2028

ECTION 2 — HAZARDS IDENTIFIC Classification of the substance of	or mixture	
classification of the substance t	of mixture	
Dangerous Goods	Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail".	
GHS Classification	Flammable Liquids - Category 2	
	Aspiration Hazard - Category 1	
	Eye Damage - Category 2B	
	Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) - Category 3	
	Specific Target Organ Toxicity - Repeated Exposure - Category 2	
Poisons Schedule	S5 (naphtha petroleum, light)	
Label elements		
GHS label pictograms		
Signal word	DANGER	
Hazard statement(s)		
• • •		
AUH066	Repeated exposure may cause skin dryness and cracking.	
11	Repeated exposure may cause skin dryness and cracking. Highly flammable liquid and vapour.	
AUH066		
AUH066 H225	Highly flammable liquid and vapour.	
AUH066 H225 H304	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways.	
AUH066 H225 H304 H320	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes eye irritation.	
AUH066 H225 H304 H320 H336	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.	
AUH066 H225 H304 H320 H336 H373	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.	
AUH066 H225 H304 H320 H336 H373 Precautionary statement(s): Ge P102 P103	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. neral Keep out of reach of children. Read carefully and follow all instructions.	
AUH066 H225 H304 H320 H336 H373 Precautionary statement(s): Ge	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. neral Keep out of reach of children. Read carefully and follow all instructions.	
AUH066 H225 H304 H320 H336 H373 Precautionary statement(s): Ge P102 P103	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. neral Keep out of reach of children. Read carefully and follow all instructions.	
AUH066 H225 H304 H320 H336 H373 Precautionary statement(s): Ge P102 P103 Precautionary statement(s): Pre	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Ineral Keep out of reach of children. Read carefully and follow all instructions. Evention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No	
AUH066 H225 H304 H320 H336 H373 Precautionary statement(s): Ge P102 P103 Precautionary statement(s): Pre	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Ineral Keep out of reach of children. Read carefully and follow all instructions. Evention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
AUH066 H225 H304 H320 H336 H373 Precautionary statement(s): Ge P102 P103 Precautionary statement(s): Pre	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. neral Keep out of reach of children. Read carefully and follow all instructions. evention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed.	
AUH066 H225 H304 H320 H336 H373 Precautionary statement(s): Ge P102 P103 Precautionary statement(s): Pre P210 P233 P240	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Ineral Keep out of reach of children. Read carefully and follow all instructions. Ineral Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment.	



SAFETY DATA SHEET SUPER SHEEN

Product Name:

Date of Issue: JULY 2023 Page 2 of Total 6

P280	Wear protective gloves, protective clothing and eye protection.	
P264	Wash hands thoroughly after handling.	
P260	Do not breathe mist, vapours or spray.	
P271	Use only outdoors or in a well-ventilated area.	
Precautionary statement(s): Res	sponse	
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.	
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.	
P301+P310	IF SWALLOWED: Immediately call a Poison Centre.	
P331	Do NOT induce vomiting.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313	If eye irritation persists: Get medical attention.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P314		
Precautionary statement(s): Sto	orage	
P403+P235	Store in a well-ventilated place. Keep cool.	
P233	Keep container tightly closed.	
P405	Store locked up.	
Precautionary statement(s): Disposal		
P501	Dispose of contents and container in accordance with local regulations.	
Note		
IMPORTANT	This SDS and the Hazard Classifications contained therein, only apply to the product in its concentrated form, as supplied.	

SECTION 3 – COMPOSITION AND INFORMATION ON INGREDIENTS			
Ingredients:	CAS Number:	Proportion (%w/w):	
Naphtha petroleum, light, hydrotreated	64742-49-0	60-90	
Polydimethylsiloxane	63148-62-9	10-30	
Ingredients determined to be non- hazardous at the concentrations used	various	balance	

SECTION 4 – FIRST AID	MEASURES
Inhalation	Remove person to fresh air away from exposure. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Obtain medical attention if symptoms occur.
Skin contact	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water. Seek medical attention.
Eye contact	Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.
Ingestion	Do NOT induce vomiting. Do NOT attempt to give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Give water to drink. If vomiting occurs, give further water to achieve effective dilution. Seek medical advice (e.g., doctor).
Advice to Doctor	Treat symptomatically.
First Aid Facilities	Eye wash station. Normal washroom facilities.



SAFETY DATA SHEET SUPER SHEEN

Product Name:

Date of Issue: JULY 2023 Page 3 of Total 6

SECTION 5 – FIRE FIGHTING	G MEASURES
Fire and Explosion	Highly flammable liquid. May be violently or explosively reactive. Avoid contamination with
Hazards	oxidising agents (i.e., nitrates, oxidising acids, chlorine bleaches, pool chlorine) as ignition may result. On combustion, may emit toxic fumes of carbon monoxide (CO).
Extinguishing Media	Use extinguishing media suitable for surrounding fires. Use a carbon dioxide (CO ₂) fire extinguisher, foam or dry chemical powder. Use water spray or fog for large fires only.
Fire Fighting	Keep any containers that are exposed to extreme heat cool with water spray. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion or decomposition. If safe, switch off electrical equipment until fire hazard removed. Prevent, by any means available, spillage from entering drains or water course.
Flash Point	35°C
Hazchem	•3YE

SECTION 6 – ACCIDENTAL RELEASE MEASURES		
Emergency Procedures	Wear PPE in accordance with Section 8 of this SDS. Minor spill: Remove all ignition sources.	
	Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Collect and	
	seal in properly labelled containers or drums for disposal.	
	Major spill: Remove all ignition sources. Prevent spillage from entering drains or water courses.	
	Wear appropriate personal protective equipment and clothing to prevent exposure. Increase	
	ventilation. As a water-based product, if spilt on electrical equipment the product will cause	
	short-circuits. If possible, contain the spill. Place inert absorbent material onto spillage. Collect	
	the material and place into a suitable labelled container. Dispose of waste according to the	
	applicable local and national regulations. If contamination of sewers or waterways occurs	
	inform the local water and waste management authorities in accordance with local regulations.	

SECTION 7 – HANDLI	NG AND STORAGE
Handling	Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Do not use in confined spaces. Avoid skin or eye contact with concentrate. Wear protective clothing when risk of exposure occurs. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Avoid naked lights, heat or ignition sources. Keep containers closed at all times. Avoid physical damage to containers. Always wash hands with water after handling. Launder contaminated clothing before re-use.
Storage	Store in a cool, dry, well-ventilated place and out of direct sunlight. DO NOT store in aeas where vapours may be trapped. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks. This material is classified as a Class 3 Flammable as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

SECTION 8 – EXPOSUR	E CONTROLS AND PERSONAL PROTECTION
Exposure Limits	National Occupational Exposure Limits, as published by Safe Work Australia: Time-weighted Average (TWA): None established for product or constituent ingredients.
Ventilation	Ensure adequate ventilation. Use of a quantity of this material in a confined space or poorly ventilated area, where rapid build-up of concentrated atmosphere may occur, could require increased ventilation and/or personal protective equipment.
Personal Protective Equipment	Use good occupational work practice. The use of protective clothing and equipment depends upon the degree and nature of exposure. The following protective equipment should be available;



SAFETY DATA SHEET

Product Name: SUPER SHEEN

Date of Issue: JULY 2023 Page 4 of Total 6

Eye Protection	Safety glasses with side shields should be used for handling concentrate in quantity, cleaning up spills, decanting, etc. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear gloves of impervious material such as PVC or neoprene rubber – to handle in quantity, clean up spills, decanting, etc. Final choice of appropriate gloves will vary according to individual circumstances. i.e., methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Suitable protective workwear, e.g., rubber apron, boots and cotton overalls buttoned at neck and wrist are recommended. A chemical-resistant apron is. recommended where large quantities are handled. Some plastic personal protective equipment (PPE) (e.g., gloves, aprons, overshoes) are not recommended as they may produce static electricity. Non-sparking safety or conductive footwear should be considered.
Respirator	If engineering controls are not effective in controlling airborne exposure, then an approved respirator with a replaceable mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES			
Physical State	Liquid	Colour	Clear
Odour	Solvent	Specific Gravity	0.7 @ 25°C
Boiling Point	>80°C	Freezing Point	Not available
Vapour Pressure	Not applicable	Vapour Density	Not available
Flash Point	35°C	Flammable Limits	1% - 6%
Water Solubility	Immiscible	рН	Not applicable

SECTION 10 – STABILITY AND REACTIVITY		
Reactivity	Highly flammable liquid and vapour. Severe fire hazard when exposed to heat, flame and/or oxidisers.	
Conditions to Avoid	Extremes of temperature and direct sunlight.	
Incompatibilities	Avoid contamination with oxidising agents (i.e., nitrates, oxidising acids, chlorine bleaches, pool chlorine etc.) as ignition may result.	
Hazardous	Thermal decomposition may result in the release of toxic and/or irritating fumes. High	
Decomposition	temperature decomposition products include silicon dioxide, small amounts of formaldehyde, formic acid, acetic acid and traces of silicon polymers.	

SECTION 11 – TOXICOLOGICAL INFORMATION	
POTENTIAL HEALTH EFFECT	rs
No adverse health effects e	expected if the product is handled in accordance with this Safety Data Sheet and the product label.
Symptoms or effects that n	nay arise if the product is mishandled and overexposure occurs are:
Inhalation	Inhalation of vapours or mists can cause drowsiness and dizziness. Exposure to high concentrations of the product in liquid form or as a mist may lead to possible harmful irritation effects.
Skin contact	Contact may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. Severity depends on the concentration and duration of exposure.
Eye contact	May cause eye irritation.
Ingestion	Swallowing may result in temporary lethargy, weakness, incoordination and diarrhoea.



SAFETY DATA SHEET

Product Name: SUPER SHEEN

Date of Issue: JULY 2023 Page 5 of Total 6

Chronic exposure	Prolonged or repeated skin exposure may cause drying with cracking, irritation and possible dermatitis following.
Toxicology Information	Non-toxic, based on ingredient calculated values.
Carcinogen Status	No significant ingredient is classified as carcinogenic by SWA.
Respiratory Sensitisation	Not expected to be a respiratory sensitizer.
Skin Sensitisation	Not expected to be a skin sensitizer.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Reproductive Toxicity	Not considered to be toxic to reproduction.
STOT-single exposure	This material has been classified as a specific hazard to target organs by single exposure.
STOT-repeated exposure	This material has been classified as a specific hazard to target organs by repeat exposure.
Aspiration Hazard	Expected to be an aspiration hazard.

SECTION 12 – ECOLOGICAL INFORMATION	
Eco-toxicity	No information
Product	
Persistence and	No information
degradability	
Bio accumulative	No information
potential	
Mobility in soil	No information
Other adverse effects	No information
Environmental Protection	Do not discharge this material into waterways.

SECTION 13 – DISPOSAL CONSIDERATIONS

Dispose of waste according to applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

SECTION 14 – TRANSPORT	TINFORMATION
ADG	Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of
	Dangerous Goods by Road & Rail".
Marine Pollutant	No
Land Transport (ADG)	
UN Number	1993
Proper Shipping Name	FLAMMABLE LIQUID, N.O.S. (CONTAINS NAPHTHA PETROLEUM, LIGHT, HYDROHEATED)
Class	3
HAZCHEM Code	•3YE
Packing Group	ll II
ERG	14
Limited Quantity	1L
Segregation	Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

SECTION 15 – REGULATORY INFORMATION	
GHS Classification	Classified as Hazardous according to the Globally Harmonised System of Classification and
	labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.
SUSMP	S5 (naphtha petroleum, light)



SAFETY DATA SHEET

Product Name: SUPER SHEEN

Date of Issue: JULY 2023 Page 6 of Total 6

ADG Code	Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail".
AICS	All ingredients present on AICS

Issue Date	July 2023
Version Number	V8: regular review
Abbreviations and	ADG Code: Australian Code for the Transport of Dangerous Goods by Road and Rail.
acronyms	AICS: Australian Inventory of Chemical Substances.
ucronyms	CAS Number: Chemical Abstracts Service Registry Number.
	GHS: Globally Harmonized System of Classification and Labelling of Chemicals
	HAZCHEM: An emergency action code of numbers and letters which gives information to emergency
	services.
	HCIS: Hazardous Chemical Information System
	SWA: Safe Work Australia.
	SDS: Safety Data Sheet
	STEL: Short Term Exposure Limit.
	SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons.
	TWA: Time Weighted Average.
	UN Number: United Nations Number.
Literature references	Preparation of Safety Data Sheets for Hazardous Chemicals – Code of Practice (Safe Work Australia)
	GHS Hazardous Chemical Information List (Safe Work Australia)
	Guidance on the Classification of Hazardous Chemicals under the WHS Regulations.
	Global Harmonized System of Classification and Labelling of Chemicals (GHS)
	"Australian Exposure Standards". Safe Work Australia
	Australian Code for The Transport of Dangerous Goods by Road and Rail
	Standard for the Uniform Scheduling of Medicines and Poisons
	Safety Data Sheets – individual raw materials – Suppliers
	HCIS – Hazardous Chemical Information System – National Safe Work Australia Data Base.
Disclaimer	This SDS summarizes at the date of issue our best knowledge of the health and safety hazard information of this product and in particular how to safely handle and use this product in the workplace. Since the supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this supplier.