Magic Wash Auto Klene Solutions

Chemwatch: **5194-93** Version No: **3.1.1.1**

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 0

Issue Date: **01/11/2019**Print Date: **05/02/2021**S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier Product name Magic Wash Chemical Name Not Applicable Synonyms Not Available Chemical formula Not Applicable Other means of identification Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Concentrated auto wash, vehicle cleaner
--------------------------	---

Details of the supplier of the safety data sheet

Registered company name	Auto Klene Solutions
Address	1/83 Merrindale Drive Croydon VIC 3136 Australia
Telephone	+61 3 8761 1900
Fax	+61 3 8761 1955
Website	http://www.autoklene.com
Email	info@autoklene.com

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

SECTION 2 Hazards identification

Classification of the substance or mixture

NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

ChemWatch Hazard Ratings

	Min	Max	
Flammability	0		
Toxicity	0		0 = Minimum
Body Contact	0	- 1	1 = Low
Reactivity	0		2 = Moderate
Chronic	0	i	3 = High 4 = Extreme

Poisons Schedule	Not Applicable
Classification [1]	Not Applicable

Label elements

Luber cicinents	
Hazard pictogram(s)	Not Applicable
Signal word	Not Applicable

Hazard statement(s)

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Issue Date: **01/11/2019**Print Date: **05/02/2021**

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available	10-30	blend of builders, water soluble solvent as
56539-66-3		3-methoxy-3-methyl-1-butanol
Not Available		anionic surfactant mixture
Not Available		perfume and dye nonhazardous
7732-18-5	balance	water

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances. In such an event consider:

- foam.
- dry chemical powder.
- carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	 The material is not readily combustible under normal conditions. However, it will break down under fire conditions and the organic component may burn. Not considered to be a significant fire risk. Heat may cause expansion or decomposition with violent rupture of containers. Decomposes on heating and may produce toxic fumes of carbon monoxide (CO). May emit acrid smoke. Decomposes on heating and produces toxic fumes of:

SECTION 6 Accidental release measures

HAZCHEM

carbon dioxide (CO2)

Not Applicable

other pyrolysis products typical of burning organic material.

Issue Date: **01/11/2019**Print Date: **05/02/2021**

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	Minor hazard. Clear area of personnel. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment as required. Prevent spillage from entering drains or water ways. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- ▶ Use in a well-ventilated area.

Safe handling

- When handling DO NOT eat, drink or smoke.
- Always wash hands with soap and water after handling.
- Avoid physical damage to containers.
- Use good occupational work practice.

Other information

- Store in original containers.
- Keep containers securely sealed.Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- ▶ Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
 Check all containers are clearly labelled and free from leaks.
- Storage incompatibility
- Avoid contamination of water, foodstuffs, feed or seed.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Magic Wash	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	
3-methoxy-3-methyl-1-butanol	Not Available		Not Available	
	Not Available		Not Available	

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating Occupational Exposure Band Limit				
3-methoxy-3-methyl-1-butanol	E	≤ 0.1 ppm			
Notes:	Occupational exposure banding is a process of assigning chemicals into sadverse health outcomes associated with exposure. The output of this processing of exposure concentrations that are expected to protect worker hea	ocess is an occupational exposure band (OEB), which corresponds to a			

Exposure controls

Appropriate engineering controls Appropriate engineering controls Controls Appropriate engineering controls Controls Appropriate engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically

Issue Date: **01/11/2019**Print Date: **05/02/2021**

"adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Personal protection No special equipment for minor exposure i.e. when handling small quantities. OTHERWISE: • Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing Eye and face protection the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Skin protection See Hand protection below No special equipment needed when handling small quantities. Hands/feet protection OTHERWISE: Wear chemical protective gloves, e.g. PVC. See Other protection below **Body protection** No special equipment needed when handling small quantities. OTHERWISE: Other protection Overalls. Barrier cream.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the $\ computergenerated$ selection:

Eyewash unit.

Magic Wash

Material	СРІ
BUTYL	A
NEOPRENE	A
VITON	A
NATURAL RUBBER	С
PVA	С

- * CPI Chemwatch Performance Index
- A: Best Selection
- B: Satisfactory; may degrade after 4 hours continuous immersion
- C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1	-
up to 50	1000	-	A-AUS / Class 1
up to 50	5000	Airline *	-
up to 100	5000	-	A-2
up to 100	10000	-	A-3
100+			Airline**

^{* -} Continuous Flow ** - Continuous-flow or positive pressure demand A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Yellow / gold liquid with citrus odour; mixes with water		
	,		
Physical state	Liquid	Relative density (Water = 1)	~1.5
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	8.0-8.5	Decomposition temperature	Not Available
Melting point / freezing point (°C)	~0	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	~100	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available

^{*} Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Issue Date: **01/11/2019**Print Date: **05/02/2021**

Vapour pressure (kPa)	2 @ 20 degC	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	Not normally a hazard due to non-volatile nature of product The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	Considered to be non toxic The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

Magic Wash	TOXICITY	IRRITATION		
Wayic Wasii	Not Available	Not Available		
	TOXICITY	IRRITATION		
3-methoxy-3-methyl-1-butanol	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]		
	Oral(Rat) LD50; 0.004 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]		
	TOXICITY	IRRITATION		
water	Oral(Rat) LD50; >90 mg/kg ^[2]	Not Available		
Legend:	Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances			

For 3-methyl-3-methoxy butanol (MMB):

3-METHOXY-3-METHYL-1-BUTANOL

Acute toxicity: In an acute dermal toxicity study with 3-methoxy-3-methyl-1-butanol (MMB) at 2000 mg/kg bw, there was no death, clinical sign or abnormality at necropsy in SD rats. The acute dermal LD50 was considered to be more than 2000 mg/kg bw. In an acute oral toxicity study [OECD TG 401], Crj:CD SD rats (5 animals/sex/dose) were given MMB by gavage at 0, 2000, 3200, 4000 or 5000 mg/kg bw for males and females. Deaths were found in males and females at 4000 mg/kg and higher. No changes in body weight were recorded for rats that died. The LD50 values were estimated to be 4500 and 4300 mg/kg bw in males and females, respectively. There is no available information on acute inhalation toxicity.

The undiluted MMB showed slight irritation to the skin after prolonged exposure in rabbits.

Magic Wash & WATER

No significant acute toxicological data identified in literature search.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legena

★ - Data either not available or does not fill the criteria for classification

🧪 – Data available to make classification

SECTION 12 Ecological information

Toxicit	١

Toxiony					
Magic Wash	Endpoint	Test Duration (hr)	Species	Value	Source

Issue Date: 01/11/2019 Print Date: 05/02/2021

	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	>100mg/L	2
3-methoxy-3-methyl-1-butanol	EC50	48	Crustacea	>1000mg/L	2
	EC50	72	Algae or other aquatic plants	>1000mg/L	2
	NOEC	504	Crustacea	100mg/L	2
	Endpoint	Test Duration (hr)	Species	Value	Source
water	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	V3.12 (QSAR		istered Substances - Ecotoxicological Informati I, Ecotox database - Aquatic Toxicity Data 5. EC		

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
3-methoxy-3-methyl-1-butanol	LOW	LOW	
water	LOW	LOW	

Bioaccumulative potential

Ingredient	Bioaccumulation
3-methoxy-3-methyl-1-butanol	LOW (LogKOW = 0.4555)
water	LOW (LogKOW = -1.38)

Mobility in soil

Ingredient	Mobility
3-methoxy-3-methyl-1-butanol	HIGH (KOC = 1)
water	LOW (KOC = 14.3)

SECTION 13 Disposal considerations

Waste treatment methods

- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required

Labels Required	
Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
3-methoxy-3-methyl-1-butanol	Not Available
water	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
3-methoxy-3-methyl-1-butanol	Not Available
water	Not Available

SECTION 15 Regulatory information

Issue Date: **01/11/2019**Print Date: **05/02/2021**

3-methoxy-3-methyl-1-butanol is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

water is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (3-methoxy-3-methyl-1-butanol; water)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 Other information

Revision Date	01/11/2019
Initial Date	25/11/2015

SDS Version Summary

	•		
Version	Issue Date	Sections Updated	
2.1.1.1	25/11/2015	Acute Health (swallowed), Engineering Control, Ingredients	
3.1.1.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification	

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.