SAFETY DATA SHEET.



Issuing date April 17, 2018 Revision Date April 17, 2018 Version 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name TOTAL RELEASE BLACK DIAMOND

Recommended use of the chemical

and restrictions on use

HT 19030 Product code

Extremely flammable aerosol Product Type

Synonyms None

Supplier's details

Recommended Use Air freshener.

Uses advised against No information available

Manufactured For: Hi-Tech Industries 33106 W. 8 Mile Farmington, MI 48336

Company Telephone: 248-358-2626

Chemical Emergency Phone

INFOTRAC 1-352-323-3500 (International)

Number 1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation

Causes serious eye irritation

May cause drowsiness or dizziness

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance Clear Physical state Aerosol Odor Solvent

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

Specific treatment (see first aid on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water.

Take off contaminated clothing and wash before reuse

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Revision Date April 17, 2018

Hazards not otherwise classified (HNOC)

None

Other information

3.9E-06% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
ACETONE	67-64-1	70-80
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
PROPYLENE GLYCOL	57-55-6	1-10

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice Avoid contact with eyes, skin, and clothing. Avoid breathing, vapors, mist, or gas.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. If symptoms persist, call a physician.

Skin contactWash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If skin irritation persists, call a physician.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen

may be necessary. If breathing has stopped, contact emergency medical services

immediately.

Ingestion Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Drink plenty of water. Call a physician or Poison Control Center immediately.

Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin irritation. Causes eye irritation. May cause respiratory irritation. May be harmful

if swallowed.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

water fog. Dry chemical. Foam. Carbon dioxide (CO2). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Keep away from heat and sources of ignition. Do not smoke. Cool containers / tanks with water spray.

Revision Date April 17, 2018

Specific hazards arising from the chemical

Extremely flammable. Keep product and empty container away from heat and sources of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

Explosion Data

Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin, and clothing. Avoid breathing vapors or mists. . Use with

adequate ventilation. Keep container away from heat,flames, and all other sources of ignition. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Wash

thoroughly after handling. Ensure adequate ventilation.

Environmental precautions

Environmental precautionsReport spills as required by local and federal regulations. Beware of vapors accumulating to

form explosive concentrations. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water

system. Prevent product from entering drains.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Soak up condensate with inert

absorbent material and collect in ventilated waste container for disposal.

Methods for cleaning up Contain liquid and collect with an inter,non-combustible material. Pick up and transfer to

properly labeled containers. Soak up with inert absorbent material. Clean contaminated

surface thoroughly. After cleaning, flush away traces with water.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not

puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid contact with skin and eyes. Avoid breathing vapors or mist. Contents under pressure. DO not puncture or incinerate container. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Do not lay on its side.

Store in a cool place.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

Incompatible products Strong acids, alkalis, or oxidizing agents.

Aerosol Level 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	Chemical Name ACGIH TLV OSHA PEL		NIOSH IDLH
ACETONE	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not apply	
		to the cellulose acetate fiber	
	indus		
		sectors	
		(vacated) STEL: 1000 ppm	
PROPANE/ISOBUTANE/N-BUTANE	74-98-6: TWA: 1000 ppm	74-98-6:TWA: 1000 ppm	74-98-6:IDLH: 2100 ppm
68476-86-8	106-97-8: STEL: 1000 ppm	TWA: 1800 mg/m ³	TWA: 1000 ppm
	75-28-5: STEL: 1000 ppm	(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	106-97-8:TWA: 800 ppm
		106-97-8: (vacated) TWA: 800	TWA: 1900 mg/m ³
		ppm	75-28-5:TWA: 800 ppm
		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992).

Exposure controls

Engineering Measures Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Odor

provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state Aerosol **Appearance** Clear

Color **Odor Threshold** clear No information available

Remarks • Methods Property Values

Hq

No information available Melting/freezing point No information available Boiling point/boiling range No information available

Flash Point -97 °C / -143 °F Based on propellant

No information available **Evaporation rate** Flammability (solid, gas) No information available

Solvent

HT 19030 TOTAL RELEASE BLACK DIAMOND

Revision Date April 17, 2018

Flammability Limits in Air

upper flammability limitNo information availablelower flammability limitNo information availableVapor pressureNo information availableVapor densityNo information available

Specific Gravity 0.762

Water solubility Practically insoluble
Partition coefficient: n-octanol/waterNo information available
Autoignition temperature No information available

Decomposition temperature No information available

ViscosityNo information availableExplosive propertiesNo information available

Other information

VOC Content(%) 18.92

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Strong acids, alkalis, or oxidizing agents.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Vapors may irritate throat and respiratory system. May cause drownsiness and dizziness

based on components. May cause irritation of respiratory tract. Avoid breathing vapors or

Not applicable

mists.

Eye contact Irritating to eyes. Avoid contact with eyes.

Skin contact Irritating to skin. Repeated exposure may cause skin dryness or cracking. Prolonged skin

contact may defat the skin and produce dermatitis. Avoid contact with skin.

Ingestion May be harmful or fatal if swallowed.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation	
ACETONE = 5800 mg/kg		20,000 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h	
67-64-1				
PROPYLENE GLYCOL	= 20000 mg/kg (Rat)	= 20800 mg/kg (Rabbit)	-	
57-55-6				

Revision Date April 17, 2018

Information on toxicological effects

Symptoms Inhalation may cause nose, throat, and respiratory tract irritation. Irritation to skin and eyes.

May be harmful if swallowed.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin. Eye damage/irritation Irritating to eyes.

Irritation Irritating to eyes, respiratory system and skin.

SensitizationNo information available.Germ Cell MutagenicityNo information available.

Carcinogenicity There are no known carcinogenic chemicals in this product.

Reproductive toxicity The ingredients are not reproductive hazards.

Specific target organ systemic toxicity (single exposure)

May cause respiratory irritation. May cause drowsiness and dizziness.

Specific target organ systemic

emic None under normal use conditions.

toxicity (repeated exposure)
Target Organ Effects

Central nervous system, Eyes, Respiratory system, Skin.

Neurological effects Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal.

Aspiration hazard Not applicable.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 3.9E-06% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 61667 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to	Toxicity to daphnia and
			microorganisms	other aquatic invertebrates
ACETONE	-	4.74 - 6.33 mL/L LC50	-	10294 - 17704 mg/L EC50
67-64-1		Oncorhynchus mykiss 96h		Daphnia magna 48h Static
		6210 - 8120 mg/L LC50		12600 - 12700 mg/L EC50
		Pimephales promelas 96h		Daphnia magna 48h
		static 8300 mg/L LC50		
		Lepomis macrochirus 96h		
PROPANE/ISOBUTANE/N-	-	-	-	-
BUTANE				
68476-86-8				
PROPYLENE GLYCOL	19000 mg/L EC50	41 - 47 mL/L LC50	-	1000 mg/L EC50 Daphnia
57-55-6	Pseudokirchneriella	Oncorhynchus mykiss 96h		magna 48h Static
	subcapitata 96h	static 51400 mg/L LC50		
		Pimephales promelas 96h		
		static 51600 mg/L LC50		
		Oncorhynchus mykiss 96h		
		static 710 mg/L LC50		
		Pimephales promelas 96h		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	log Pow

HT 19030 TOTAL RELEASE BLACK DIAMOND

Revision Date April 17, 2018

ACETONE 67-64-1	-0.24
PROPANE/ISOBUTANE/N-BUTANE	2.8
68476-86-8	

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations. This material, as

supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Ground CONSUMER COMMODITY ORM-D

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
ACETONE	Х	X	X	Χ	Х	X	X	Х
PROPANE/ISOBUTAN E/N-BUTANE	Х	Х	Х	Not listed	Х	Х	Х	Х
PROPYLENE GLYCOL	Х	Х	X	Х	Х	Х	X	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health HazardYesChronic Health HazardYesFire HazardYesSudden Release of Pressure HazardYesReactive Hazardno

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any known Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE	X	X	X
67-64-1			
PROPYLENE GLYCOL	X		X
57-55-6			

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

A Compressed gases B5 Flammable aerosol D2B Toxic materials



NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical hazards HMIS Health Hazard 2 Flammability 4 Physical Hazard 1 Personal protection B

HT 19030 TOTAL RELEASE BLACK DIAMOND

Revision Date April 17, 2018

Prepared By Regulatory Affairs Issuing date April 17, 2018 Revision Date April 17, 2018

Revision Note

No information available

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet