# SAFETY DATA SHEET.



Issuing date April 17, 2018 Revision Date April 17, 2018 Version 1.01

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name TOTAL RELEASE SEA BREEZE

Recommended use of the chemical

and restrictions on use

Product code HT 19035

Product Type Extremely flammable aerosol

Synonyms None

Supplier's details

Recommended Use Air freshener.

Uses advised against No information available

Manufactured For: Hi-Tech Industries 33106 W. 8 Mile

Farmington, MI 48336

Company Telephone: 248-358-2626

Chemical Emergency Phone INFOTRAC 1-352-323-3500 (International)

**Number** 1-800-535-5053 (North America)

# 2. HAZARDS IDENTIFICATION

#### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

# GHS Label elements, including precautionary statements

#### **Emergency Overview**

#### DANGER

#### **Hazard Statements**

Causes skin irritation Causes serious eye irritation May cause drowsiness or dizziness

Extremely flammable aerosol

Contains gas under pressure; may explode if heated



Appearance Clear Physical state Aerosol Odor Solvent

# **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

#### **Precautionary Statements - Response**

Specific treatment (see first aid on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water.

Take off contaminated clothing and wash before reuse

If skin irritation occurs: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell

# **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Revision Date** April 17, 2018

# Hazards not otherwise classified (HNOC)

None

#### Other information

3.9E-06% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
ACETONE	67-64-1	70-80
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
PROPYLENE GLYCOL	57-55-6	1-10

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

## First aid measures for different exposure routes

**General advice** Avoid contact with eyes, skin, and clothing. Avoid breathing, vapors, mist, or gas.

**Eye contact** Rinse thoroughly with plenty of water for at least 15 minutes. Consult a physician if irritation

persists. Keep eye wide open while rinsing. If symptoms persist, call a physician.

**Skin contact**Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If skin irritation persists, call a physician.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen

may be necessary. If breathing has stopped, contact emergency medical services

immediately.

Ingestion Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Drink plenty of water. Call a physician or Poison Control Center immediately.

# Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin irritation. Causes eye irritation. May cause respiratory irritation. May be harmful

if swallowed.

# Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

#### **Suitable Extinguishing Media**

water fog. Dry chemical. Foam. Carbon dioxide (CO2). Cool containers / tanks with water spray.

**Unsuitable Extinguishing Media** Keep away from heat and sources of ignition. Do not smoke. Cool containers / tanks with water spray.

Revision Date April 17, 2018

Specific hazards arising from the chemical

Flammable or extremely flammable aerosol. Container may burst in fire. Extremely flammable. Risk of ignition. In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray. Keep product and empty container away from heat and sources of ignition.

# **Explosion Data**

Sensitivity to Mechanical Impact none.
Sensitivity to Static Discharge Yes.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

#### 6. ACCIDENTAL RELEASE MEASURES

# Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin, and clothing. Avoid breathing vapors or mists. . Use with

adequate ventilation. Keep container away from heat,flames, and all other sources of ignition. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Wash

thoroughly after handling . Ensure adequate ventilation.

**Environmental precautions** 

**Environmental precautions**Report spills as required by local and federal regulations. Beware of vapors accumulating to

form explosive concentrations. Vapors can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water

system.

Methods and materials for containment and cleaning up

**Methods for Containment**Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Contain liquid and collect with an inter,non-combustible material. Pick up and transfer to

properly labeled containers. Soak up with inert absorbent material. Clean contaminated

surface thoroughly. After cleaning, flush away traces with water.

#### 7. HANDLING AND STORAGE

# Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not

puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid contact with skin and eyes. Avoid breathing vapors or mist. Contents under pressure. DO not puncture or incinerate container. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Do not lay on its side.

Store in a cool place.

Conditions for safe storage, including any incompatibilities

**Technical measures/Storage** 

conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out

of the reach of children. Store locked up.

**Incompatible products** Strong acids, alkalis, or oxidizing agents.

Aerosol Level 3

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control parameters**

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE	STEL: 750 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 500 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	_
		(vacated) STEL: 2400 mg/m <sup>3</sup>	
		The acetone STEL does not apply	
		to the cellulose acetate fiber	
		industry. It is in effect for all other	
	sectors		
		(vacated) STEL: 1000 ppm	
PROPANE/ISOBUTANE/N-BUTANE	74-98-6: TWA: 1000 ppm	74-98-6:TWA: 1000 ppm	74-98-6:IDLH: 2100 ppm
68476-86-8	106-97-8: STEL: 1000 ppm	TWA: 1800 mg/m <sup>3</sup>	TWA: 1000 ppm
	75-28-5: STEL: 1000 ppm	(vacated) TWA: 1000 ppm	TWA: 1800 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	106-97-8:TWA: 800 ppm
		106-97-8: (vacated) TWA: 800	TWA: 1900 mg/m <sup>3</sup>
		ppm	75-28-5:TWA: 800 ppm
		(vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 1900 mg/m <sup>3</sup>
			ļ

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d **Other Exposure Guidelines** 

962 (11th Cir., 1992).

**Exposure controls** 

**Engineering Measures** Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses with side-shields.

Skin and body protection Chemical resistant apron. Protective gloves.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Handle in accordance with good industrial hygiene and safety practice. Hygiene measures

# 9. PHYSICAL AND CHEMICAL PROPERTIES

## Physical and chemical properties

Physical state Aerosol **Appearance** Clear

Odor Solvent Color

clear **Odor Threshold** No information available

**Property** Values Remarks • Methods

No information available На Melting/freezing point No information available Boiling point/boiling range No information available

**Flash Point** -97 °C / -143 °F Based on propellant

**Evaporation rate** No information available

# HT 19035 TOTAL RELEASE SEA BREEZE

Revision Date April 17, 2018

Flammability (solid, gas) No information available

Flammability Limits in Air

upper flammability limit No information available lower flammability limit No information available Vapor pressure No information available Vapor density No information available

**Specific Gravity** 0.762

Water solubility Practically insoluble Partition coefficient: n-octanol/waterNo information available No information available **Autoignition temperature** 

**Decomposition temperature** No information available

**Viscosity** No information available **Explosive properties** No information available

Other information

VOC Content(%) 18.92

# 10. STABILITY AND REACTIVITY

Reactivity

No data available

**Chemical stability** 

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

**Conditions to Avoid** 

Extremes of temperature and direct sunlight.

**Incompatible Materials** 

Strong acids, alkalis, or oxidizing agents.

**Hazardous Decomposition Products** 

Carbon oxides.

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

#### **Product Information**

Inhalation Vapors may irritate throat and respiratory system. May cause drownsiness and dizziness

based on components. May cause irritation of respiratory tract. Avoid breathing vapors or

Not applicable

mists.

Eye contact Irritating to eyes. Avoid contact with eyes.

Skin contact Irritating to skin. Prolonged skin contact may defat the skin and produce dermatitis.

Ingestion May be harmful if swallowed.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
ACETONE 67-64-1	= 5800 mg/kg	20,000 mg/kg (Rabbit)	$= 50100 \text{ mg/m}^3 \text{ (Rat) 8 h}$
PROPYLENE GLYCOL 57-55-6	= 20000 mg/kg (Rat)	= 20800 mg/kg (Rabbit)	-

\_\_\_\_\_

#### Information on toxicological effects

**Symptoms** Inhalation may cause nose, throat, and respiratory tract irritation. Irritation to skin and eyes.

May be harmful if swallowed.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin. Eye damage/irritation Irritating to eyes.

Irritation Irritating to eyes, respiratory system and skin.

Sensitization None known.

Germ Cell Mutagenicity None known.

**Carcinogenicity** There are no known carcinogenic chemicals in this product.

**Reproductive toxicity** The ingredients are not reproductive hazards.

Specific target organ systemic toxicity (single exposure)

may cause drowsiness and dizziness. May cause respiratory irritation.

Specific target organ systemic

toxicity (repeated exposure)
Chronic toxicity

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and

potential cardiac arrest.

None under normal use conditions.

Target Organ Effects Ce

Central nervous system, Eyes, Respiratory system, Skin. Not applicable.

Aspiration hazard Not applicable.

# Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 3.9E-06% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document ...

ATEmix (oral) 61667 mg/kg

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
ACETONE 67-64-1	-	4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h	-	10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h
PROPANE/ISOBUTANE/N- BUTANE 68476-86-8	-	-	-	-
PROPYLENE GLYCOL 57-55-6	19000 mg/L EC50 Pseudokirchneriella subcapitata 96h	41 - 47 mL/L LC50 Oncorhynchus mykiss 96h static 51400 mg/L LC50 Pimephales promelas 96h static 51600 mg/L LC50 Oncorhynchus mykiss 96h static 710 mg/L LC50 Pimephales promelas 96h	-	1000 mg/L EC50 Daphnia magna 48h Static

# Persistence and degradability

No information available.

#### Bioaccumulation

No information available.

Chemical Name	log Pow

#### HT 19035 TOTAL RELEASE SEA BREEZE

Revision Date April 17, 2018

ACETONE 67-64-1	-0.24
PROPANE/ISOBUTANE/N-BUTANE	2.8
68476-86-8	

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

**Waste treatment** 

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations. This material, as

supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging** Do not re-use empty containers.

# 14. TRANSPORT INFORMATION

**DOT Ground** CONSUMER COMMODITY ORM-D

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, 2.1, LTD. QTY.

# 15. REGULATORY INFORMATION

# International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
ACETONE	Х	X	X	Χ	X	Χ	X	Х
PROPANE/ISOBUTAN E/N-BUTANE	Х	Х	Х	Not listed	Х	Х	Х	Х
PROPYLENE GLYCOL	Х	Х	X	Х	Х	Х	X	Х

# Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

#### SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard Yes
Reactive Hazard no

#### **Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

# **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Chemical Name Hazardous Substances RQs		RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

# U.S. State Regulations

# **California Proposition 65**

This product does not contain any known Proposition 65 chemicals.

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	
ACETONE	ACETONE X X		X	
67-64-1				
PROPYLENE GLYCOL X			X	
57-55-6				

EPA Pesticide Registration Number Not applicable

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

#### **WHMIS Hazard Class**

A Compressed gases B5 Flammable aerosol D2B Toxic materials



# NFPA Health Hazard 2 Flammability 4 Instability 0 Physical and chemical hazards HMIS Health Hazard 2 Flammability 4 Physical Hazard 1 Personal protection B

#### HT 19035 TOTAL RELEASE SEA BREEZE

Revision Date April 17, 2018

Prepared By Regulatory Affairs Issuing date April 17, 2018 Revision Date April 17, 2018

**Revision Note** 

No information available

**Disclaimer** 

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**